

Technical details

| Mobile model | | JUNIOR TI | SUPER | SPECIAL 2 | MAXI-4 | |
|---|--------|-----------|---------|-----------|----------|-------|
| Voltage | V | 400 | 400 | 400 | 400 | |
| Current consumption | A | 9,1 | 14 | 27,3 | 54,7 | |
| Output | kW | 6 | 9 | 18 | 36 | |
| Thermal output | kcal/h | 5.000 | 7.700 | 15.462 | 30.924 | |
| Operating pressure | bar | 8 | 10 | 10 | 10 | |
| Number of steam generators | | 1 | 1 | 2 | 4 | |
| Steam output | kg/h | 7 | 12,8 | 25,7 | 51,4 | |
| Temperature in the generator | °C | 170° | 180° | 180° | 180° | |
| Temperature at the nozzle exit (steam) | °C | 100:145 | 110:150 | 120:150 | 120:150 | |
| Temperature at the nozzle exit (steam + additive) | °C | ca. 73° | ca. 73° | ca. 100° | ca. 100° | |
| Water storage tank | l | 15 | 50 | 110 | 2 x 50 | |
| Additional product storage tank | l | 1,4 | 1,4 | 2 x 1,4 | 5 | |
| Water consumption | l/h | 8 | 13 | 25 | 50 | |
| Maximum hose length | m | 10 | 18 | 20 | 36 | |
| Time from switching on to standby | min | 4 | 4 | 4 | 4 | |
| Working hours per day | h | 24 | 24 | 24 | 24 | |
| Preparation for extraction | | SERIE | SERIE | SERIE | SERIE | |
| Dimensions | Length | mm | 660 | 880 | 1.055 | 1.390 |
| | Width | mm | 400 | 520 | 700 | 900 |
| | Height | mm | 735 | 910 | 815 | 1.050 |
| | Weight | kg | 56 | 80 | 165 | 257 |

| Stationary model | | GIOVE | 9 kW | 18 kW | 36 kW | 72 kw |
|---|--------|---------|---------------------|----------|----------|-------|
| Voltage | V | 400 | 400 | 400 | 400 | 400 |
| Current consumption | A | 14 | 27,3 | 54,7 | 109,4 | |
| Output | kW | 9 | 18 | 36 | 72 | |
| Thermal output | kcal/h | 7.700 | 15.462 | 30.924 | 61.848 | |
| Operating pressure | bar | 10 | 10 | 10 | 10 | |
| Number of steam generators | | 1 | 2 | 4 | 8 | |
| Steam output | kg/h | 12,8 | 25,7 | 51,4 | 102,8 | |
| Temperature in the generator | °C | 180° | 180° | 180° | 180° | |
| Temperature at the nozzle exit (steam) | °C | 110:150 | 120:150 | 120:150 | 120:150 | |
| Temperature at the nozzle exit (steam + additive) | °C | ca. 73° | ca. 100° | ca. 100° | ca. 100° | |
| Additional product storage tank | l | | Depending on design | | | |
| Water consumption | l/h | 13 | 25 | 50 | 100 | |
| Maximum hose length | m | 18 | 20 | 36 | 36 | |
| Time from switching on to standby | min | 4 | 4 | 4 | 4 | |
| Working hours per day | h | 24 | 24 | 24 | 24 | |
| Preparation for extraction | | | Depending on design | | | |
| Dimensions | | | Depending on design | | | |



Batech Industries et Collectivités
 9, Parc d'Activités des Colonnes
 1, rue Gustave Eiffel,
 95130 Le Plessis Bouchard - France



Téléphone : 00 33 (0)1 34 44 89 89
 Télécopie : 00 33 (0)1 34 14 54 37
 Site : www.batech.fr / Courriel : contact@batech.fr